



# White Knight

## Rust Guard Fish Oil Fact Sheet

---

White Knight Fish Oil is a deodorised rust inhibiting formulation. The penetrating quality of White Knight Fish Oil actively saturates rust scale and removes moisture, forming a protective coating on metal.

### Suitable Surfaces

Fish Oil is ideal for use in inaccessible, rust prone areas such as joints, cracks and crevices.

### Preparation

All loose material and rust scale must be removed either by wire brushing, scraping or sanding. The surface must be thoroughly cleaned and free from grease, oil, dirt and other surface contaminants. Do not use when the air or surface temperature is below 15°C or above 30°C. **BEFORE SPRAYING** Cover all necessary areas to protect from overspray. It is essential to shake the can for at least one minute after mixing ball rattles to ensure product uniformity. Shake can occasionally during use. Do not use when the air or surface temperature is below 15°C or above 30°C or in excessive humidity.

### Application Details

#### Brush On

Brush On: Stir thoroughly before and during use. Apply liberal amounts of Fish Oil to completely saturate the surface. Allow Fish Oil to penetrate well into all crevices. Do not apply Fish Oil to wet or damp surfaces. Apply by brush, roller or spray Aerosol

Aerosol: Spray outside or in a well ventilated area away from fire and heaters. Test spray first on a small inconspicuous area to ensure surface compatibility and finish suitability. Hold the can upright approximately 15-20 cm from the surface. Press button firmly. Spray with a smooth sweeping motion. Apply a pre-wetting mist coat followed by a full even coat. Overlap each spray pass. Repeat if necessary. To prevent paint sagging, avoid spraying too close to the surface or spraying too heavy a coat. For hard to reach areas, place the extension tube firmly into the centre of the spray nozzle. This will allow accurate application to desired surface. Apply sufficient amounts of Fish Oil to completely saturate the surface. Allow Fish Oil to penetrate well into all crevices.

### Coverage

Brush On Up to 10 square metres per litre depending on the nature of the surface. Aerosol Up to 1 to 1.5 square metres per unit depending on amount of overspray and spraying technique.

### Drying Times

Touch dry minimum 48 hours.

### Clean Up

Overspray can be removed while still wet with mineral turps. Clean equipment and brushes with mineral turps immediately after use. Important Soak any cloths used, in water immediately after use as they may self ignite.

### Health and Safety

Refer to Material Safety Data Sheet available by request on 131 686.

### After Spraying

To clean the nozzle after use and prevent blocking turn the can upside down and press button until only gas escapes. After Spraying: To clean nozzle after use and prevent blocking, turn can upside down and press button until only gas escapes.

### Overcoating

For subsequent coats of Fish Oil apply after 7 days. For areas that are accessible or require decoration, do not use White Knight Rust Guard Fish Oil, use White Knight Rust Guard Epoxy Enamel following instructions on the label.

### Pack Sizes

500ml, 1 Litre, 4 Litre, 300g spray

### Re-Coat

Brush On: After 7 days Aerosol: After 72 hours. Drying times will be slower in cold or humid conditions, in the absence of ventilation or where heavy film builds are applied.

### HANDY HINT

Rust protection for hidden areas such as seams or inside box sections or areas that cannot be painted by conventional means.

### Got more questions? Need help? Want a brochure? Any comments or suggestions on the site?

---

If you have any comments or questions on the White Knight range or want more information we are here to help.

### Contact Us

#### Customer Care Advisers

Phone 131 686

Fax 1800 676 756

Opening Hours: Mon-Fri 8am to 7pm EST, Sat/Sun 9am to 4pm EST

Email [info@whiteknightpaints.com.au](mailto:info@whiteknightpaints.com.au)