



# White Knight

## Natural Timber Finish Fact Sheet

---

White Knight Natural Timber Finish is a semi transparent stain formulated to protect and enhance exterior and interior timber. Natural Timber Finish adds colour while highlighting the natural grain of the timber.

### Suitable Surfaces

Natural Timber Finish is the ideal protective coating for pergolas, timber cladding, weatherboards, windows, fences, doors and garden furniture.

### Preparation

The surface must be clean, dry and free from dust, dirt, grease oil and other contaminants. Treat any mould with a suitable anti-mould solution prior to application. Fill nail holes and cracks with appropriate timber putty and sand smooth. New Timber: Allow new green timber to season approximately 6 months before application. The surface may be lightly sanded with a fine grade sandpaper, followed by dusting, or left in its original rough sawn condition. No primer or undercoat is required.

### Application Details

Stir thoroughly with a broad, flat stirrer in a circular lifting motion for at least 5 minutes before use. Stir at regular intervals during application. Apply at least two coats to a correctly prepared surface using a brush, roller or spray. Final brush strokes should be made with the grain to evenly distribute the finish. To prevent runs, avoid overloading the brush. Lightly sand between coats for a smooth even finish. Durability of Natural Timber Finish improves with depth of colour and number of coats applied. A minimum of 3 - 4 coats are required if the product is supplied in an untinted state. Do not use when the air or surface temperature is below 10°C or above 30°C.

### Coverage

Up to 14 square metres per litre on smooth timber, and up to 7 square metres per litre on rough sawn timber.

### Drying Times

Touch dry 4 hours. Re-Coat: After 16 hours. Drying times will be slower in cold or humid conditions, in the absence of ventilation or where heavy film builds are applied.

### Pack Sizes

1 Litre, 4, litre, 10 litre

### Health and Safety

Refer to Material Safety Data Sheet available by request on 131 686.

### Clean Up

Mineral turps.

---

## Got more questions? Need help? Want a brochure? Any comments or suggestions on the site?

If you have any comments or questions on the White Knight range or want more information we are here to help.

### Contact Us

#### Customer Care Advisers

Phone 131 686  
Fax 1800 676 756  
Opening Hours: Mon-Fri 8am to 7pm EST, Sat/Sun 9am to 4pm EST  
Email [info@whiteknightpaints.com.au](mailto:info@whiteknightpaints.com.au)