



White Knight

Pot Belly Black Fact Sheet

White Knight Pot Belly Black is a self-priming paint designed for metal surfaces subject to radiant heat, such as pot belly stoves, ovens and barbecue surrounds. The attractive, low lustre finish is heat resistant to 300°C.

Suitable Surfaces

Pot Belly Black is ideal for Pot Belly stoves, heaters, ovens and barbecue surrounds. NOTE: Not suitable for use on BBQ heating Not suitable for food preparation surfaces.

Preparation

The surface must be thoroughly cleaned, dry and free from grease, oil, dirt, rust scale and other contaminants. Thoroughly sand new metal and lightly sand previously painted surfaces to ensure maximum adhesion. Remove loose rust and flaking paint with a wire brush, scraper or mechanical sander back to bare metal. Clean and allow to dry before painting. BEFORE SPRAYING Cover all necessary areas to protect from overspray. It is essential to shake the can for at least one minute after mixing ball rattles to ensure product uniformity. Shake can occasionally during use. Do not use when the air or surface temperature is below 15°C or above 30°C or in excessive humidity.

Application Details

Aerosol Spray outside or in a well ventilated area away from fire and heaters. Test spray first on a small inconspicuous area to ensure surface compatibility and finish suitability. Hold the can upright approximately 15-20 cm from the surface. Press button firmly. Spray with a smooth sweeping motion. Apply a pre-wetting mist coat followed by a full even coat. Overlap each spray pass. Repeat if necessary. To prevent paint sagging, avoid spraying too close to the surface or spraying too heavy a coat. After Spraying: To clean the nozzle after use and prevent blocking, turn the can upside down and press button until only gas escapes. Brush on: Stir thoroughly with a broad, flat stirrer in a circular lifting motion for at least 5 minutes before use. Stir at regular intervals during application. Apply 2 coats. Do not use when the air or surface temperature is below 10°C or above 30°C.

Coverage

Aerosol: Up to 1 - 1.5 square metres per unit depending on the nature of the surface and the amount of overspray. Brush on: Up to 16 square metres per litre depending on the nature of the surface.

Drying Times

Touch dry Aerosol: 1 hour. Brush on: Touch dry 1 hour Re-Coat: Aerosol: After 16 hours Brush on: After 16 hours Full Cure: Hard, dry conditions are achieved when the coated article is heated. Increase heat slowly the first time to prevent blistering. Drying times will be slower in cold or humid conditions, in the absence of ventilation or where heavy film builds are applied

Clean Up

no info provided

Pack Sizes

300g spray

Health and Safety

Refer to Material Safety Data Sheet available by request on 131 686.

HANDY HINT

Pot Belly Black can be applied to metal surface subjected to temperatures up to 320°C. Produces a black low sheen finish. Can be used BBQ surrounds subjected to high temperature. Do not use on food contact areas.

Got more questions? Need help? Want a brochure? Any comments or suggestions on the site?

If you have any comments or questions on the White Knight range or want more information we are here to help.

Contact Us

Customer Care Advisers

Phone 131 686

Fax 1800 676 756

Opening Hours: Mon-Fri 8am to 7pm EST, Sat/Sun 9am to 4pm EST

Email info@whiteknightpaints.com.au