



White Knight

Rust Guard Rust Converter Fact Sheet

White Knight RUST CONVERTER is a fast and effective treatment for lightly rusted steel surfaces. The advanced formulation chemically reacts with the rusty surface creating a lasting barrier against further corrosion. Ideal for small jobs where rust cannot be easily removed.

Suitable Surfaces

Lightly rusted steel.

Preparation

Remove all loose rust, scale and flaking paint by wire brushing, scraping or mechanically sanding. The surface must be clean, dry and free from grease, dirt, oil and other contaminants before applying White Knight Rust Converter.

Application Details

Stir contents thoroughly for 5 minutes before use. Pour only into plastic or glass containers and do not return leftovers to original container. Apply undiluted by brush to the rust affected area only. Wipe off any excess on surrounding metal or paintwork immediately with a damp cloth. Do not use when the air or surface temperature is below 10°C or above 30°C. Rust Converter should only be applied to rusted surfaces and is not recommended as a rust preventative coating on clean steel.

Over-coat with White Knight Rustguard Epoxy Enamel after 2 hours drying. When using a water-based or oil based topcoats, treated surfaces should first be primed with White Knight Metal Primer. Do not overcoat with White Knight Cold Gal or zinc rich primers.

Coverage

Up to 14 square metres per litre depending on the nature of the surface.

Drying Times

Touch dry in 30 minutes. Allow 2 hours for complete reaction to take place before overcoating. Drying will be slower in cold or humid conditions or in the absence of ventilation.

Clean Up

Clean brushes and equipment with water immediately after use.

Pack Sizes

50ml, 125ml, 500ml, 1 litre, 4 litre

Health and Safety

Refer to Material Safety Data Sheet available by request on 131 686.

HANDY HINT

Rust Converter kills the rust and offers superior results compared to just painting over the rust. Use over lightly rusty surface, heavy rust should be removed by mechanical means prior to use.

Got more questions? Need help? Want a brochure? Any comments or suggestions on the site?

If you have any comments or questions on the White Knight range or want more information we are here to help.

Contact Us

Customer Care Advisers

Phone 131 686

Fax 1800 676 756

Opening Hours: Mon-Fri 8am to 7pm EST, Sat/Sun 9am to 4pm EST

Email info@whiteknightpaints.com.au