



# White Knight

## Rust Guard Structural Steel Silver Fact Sheet

---

White Knight RUST GUARD STRUCTURAL STEEL SILVER is a rust preventative paint that gives the appearance of structural steel (Duragal® and Zincalume®). It is a high performance silver finish that is suitable for covering welds and joins in structural steel.

### Preparation

The surface must be thoroughly cleaned, dry and free from grease, oil, dirt, rust scale and other contaminants. Remove all loose material and grind welds back to clean metal. Degrease with White Knight Rust Guard Solvent or turps. In severe conditions, prime bare steel with White Knight Rust Guard Cold Gal before coating with White Knight Rust Guard Structural Steel Silver.

### Application Details

White Knight Rust Guard Structural Steel Silver may be applied by brush, roller or spray. Stir thoroughly with a broad, flat stirrer in a circular lifting motion for at least 5 minutes before use. Stir at regular intervals during application. Do not use when the air or surface temperature is below 10°C or above 30°C. Spraying Cover all necessary areas to protect from overspray. White Knight Rust Guard Structural Steel Silver is ready for use but may be thinned up to 10% with Rust Guard Solvent if necessary. Apply a prewetting mist coat, allow to flash off for two minutes, then apply a full even coat. Overlap each spray pass. Repeat if necessary. It is better to spray several light coats rather than one heavy coat. To prevent paint sagging, avoid spraying too close to the surface or spraying too heavy a coat.

### Coverage

Coverage Up to 10 square metres per litre depending on the surface and method of application. Note: When spraying, allow for losses on overspray.

### Drying Times

Dry Time Touch dry in 15 minutes. Recoat after 1 hour. Drying will be slower in cold or humid conditions, in the absence of ventilation or where heavy film builds are applied.

### Clean Up

Clean Up Clean brushes and equipment with White Knight Rust Guard Solvent immediately after use.

### Health and Safety

KEEP OUT OF REACH OF CHILDREN • Do not swallow • Highly Flammable. Eliminate any source of ignition. Do not smoke. Aluminium based paints may develop pressure in storage. Open the container carefully and wear gloves and eye protection. Do not allow water to contaminate the paint as this will cause build up of pressure in the can. • Irritating to eyes. • Repeated exposure may cause skin dryness or cracking. • Vapours may cause drowsiness and dizziness. Take precautionary measures against static discharges. • Keep in a cool place out of the sun. Do not store above 50°C. FIRST AID DIRECTIONS If swallowed: Do NOT induce vomiting. Drink plenty of water and seek medical advice. Eye contact: If in eyes, hold eyes open, flood with water for at least 15 minutes and seek medical advice. Skin contact: Wash affected areas with soap and water. Seek medical attention if irritation persists. For 24 hour emergency response service in Australia call 1800 807 001 and in New Zealand 0800 600 020 PROTECT OUR ENVIRONMENT Do not pour unwanted paint down the drain. Keep unwanted paint in sealed containers for disposal via special chemical waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first. PROVIDE ADEQUATE VENTILATION DURING USE AND WHILE DRYING.

---

### Got more questions? Need help? Want a brochure? Any comments or suggestions on the site?

If you have any comments or questions on the White Knight range or want more information we are here to help.

### Contact Us

#### Customer Care Advisers

Phone 131 686  
Fax 1800 676 756  
Opening Hours: Mon-Fri 8am to 7pm EST, Sat/Sun 9am to 4pm EST  
Email [info@whiteknightpaints.com.au](mailto:info@whiteknightpaints.com.au)