



White Knight

Stain Stop Sealer Fact Sheet

White Knight Stain Stop Sealer is a high opacity primer sealer specifically formulated to give excellent stain suppressing and sealing qualities. The exceptional hiding and adhesion properties ensure the product effectively seals smoke and water stains as well as lipstick, crayon, graffiti, grease marks and tannin marks. The convenient spray application makes it ideal for hard to reach areas.

Suitable Surfaces

White Knight Stain Stop Sealer can be applied under oil and water based top coats on exterior and interior surfaces.

Preparation

Remove as much of the stain as possible by washing with sugar soap, sanding or scraping. Fill nail holes, cracks and blemishes after applying one coat of Stain Stop Sealer. Spot prime these areas again before application of topcoat. Porous Surfaces: Surfaces such as bare plasterboard, timber and ceiling tiles must be thoroughly cleaned and free from all contaminants such as grease, dirt, wax and mould. Lightly sand the surface and dust down. Previously Painted Surfaces: Remove all loose and flaking paint and remove old chalky paint by washing with detergent, sanding or scraping. Thoroughly sand glossy or enamel surfaces.

BEFORE SPRAYING: Cover all necessary areas to protect from overspray. It is essential to shake the can for at least one minute after mixing ball rattles to ensure product uniformity. Shake can occasionally during use. Do not use when the air or surface temperature is below 15°C or above 30°C or in excessive humidity.

Application Details

Spray outside or in a well ventilated area away from fire and heaters. Test spray first on a small inconspicuous area to ensure surface compatibility and finish suitability. Hold the can upright approximately 20-25 cm from the surface. Press button firmly. Spray with a smooth sweeping motion. Apply a pre-wetting mist coat followed by a full even coat. Overlap each spray pass. For badly stained areas a second application may be necessary. To prevent paint sagging, avoid spraying too close to the surface or spraying too heavy a coat. After Spraying: To clean nozzle after use and prevent blocking, turn can upside down and press button until only gas escapes.

Coverage

Up to 1 - 1.5 square metres per unit depending on the nature of the surface and the amount of overspray.

Drying Times

Touch dry 10 minutes. Recoat after 2 hours. Drying times may be extended in low temperature and high humidity.

Pack Sizes

300g spray

Health and Safety

Refer to Material Safety Data Sheet available by request on 131 686.

HANDY HINT

Great for holding back watermarks and many other types of household stains prior to repainting.

Got more questions? Need help? Want a brochure? Any comments or suggestions on the site?

If you have any comments or questions on the White Knight range or want more information we are here to help.

Contact Us

Customer Care Advisers

Phone 131 686

Fax 1800 676 756

Opening Hours: Mon-Fri 8am to 7pm EST, Sat/Sun 9am to 4pm EST

Email info@whiteknightpaints.com.au